



## CSU 502 ➤ Controller

### Product Feature

- Optimized and compact power system controller
- User interface with LCD display and control stick
- User configurable alarms and settings
- Advanced battery management and testing

## Specifications

1. Input	
Mains voltage	35 – 60 V <sub>DC</sub>
Current	0.25 ADC (max.)
Protection / Switch	Internal fuse 0.75A / None
2. General	
Dimensions (W x H x D)	43 x 40.5 x 182 mm (1.7 x 1.6 x 7.1 in)
Weight	0.2 kg / 0.4 lb
3. Standards	
Safety	Approved with system
EMC	EN 55022, class B; ETSI EN 300386 compliant
Cooling	Natural air flow
Operating temperature	-40 to +65 °C (+40 to +149 °F)
Relative humidity	95%, non-condensing
4. Function	
System	User configurable alarms and settings LVD and PLD functions (1 as standard, additional 2 as option) Configurable alarm relays Built-in real time clock (option) Event log for 400 entries with time and date (option) Fan speed control for outdoor system application (option)
Battery	Temperature compensated float charge Boost and equalize charge Charging current limitation Low voltage disconnection Automatic capacity test
Rectifier	Individual rectifier information and control Efficiency mode / Energy saving Remote control and voltage adjustment by controller
5. Feature	
Rectifier interface	Digital, CAN-based
Number of rectifiers	Up to 16
Relay output	Up to 6
Temperature	Up to 2
Voltage, current	Voltage, load current, battery current
Display	96 *94 pixel LCD display
Local monitoring	USB / Delta ARMs software
Remote monitoring	Dry contacts / optional WEB server / SNMP
Remote alarming	Dry contacts / optional SNMP
6. User Interface	
Local user interface	2 LEDs LCD display Control stick
Communication	Mini-B USB port
Language	English, Traditional Chinese and Japanese
Web server	Option
SNMP	Option
6. Ordering information	
CSU 502 ID:A1	CSU 502 can version

\*All specifications are subject to change without prior notice.

Delta Group Website:  
[www.deltaww.com](http://www.deltaww.com)

Product Website:  
[www.deltapowersolutions.com](http://www.deltapowersolutions.com)

### United States of America & Canada

Delta Greentech (USA) Corp.  
2360 Campbell Creek Blvd. #530  
Richardson (Texas) 75082

### Central America

Delta Electronics International  
Mexico, S.A. de C.V.  
Via Gustavo Baz No. 2160  
Col. Industrial La Loma Tlainepartla  
CP 54060, Edo de Mexico

### South America

Delta Greentech (Brasil) S.A  
Rua Itapeva, 26 - 3 andar - Bela  
Vista  
01332-000 - São Paulo - SP - Brasil

### Asia Pacific

Delta Electronics, Inc.  
3 Tungyuan Road, Chungli Industrial  
Zone,  
Taoyuan County 32063, Taiwan

### China

Delta Electronics (Shanghai) Co., Ltd  
No.182 Minyu Road, Pudong  
Shanghai, P.R.C., China

### Japan

Delta Electronics (Japan), Inc  
2-1-14 Minato-ku shibadamin, Tokyo  
105-0012, Japan

### Russia

Delta Energy Systems LLC  
Vereyskaya Plaza II, office 401  
121357 Moscow, Russia

### Europe

Delta Energy Systems (Switzerland)  
AG  
Freiburgstrasse 251  
3010 Bern-Bümpliz, Switzerland